

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?><polycomConfig xmlns:xsi="http://www.w3.org/2001/
XMLSchema-instance" xsi:noNamespaceSchemaLocation="polycomConfig.xsd">
```

```
<tone>
```

```
<tone.dtmf
```

```
tone.dtmf.level="-15"
```

```
tone.dtmf.onTime="50"
```

```
tone.dtmf.offTime="50"
```

```
tone.dtmf.chassis.masking="0"
```

```
tone.dtmf.rfc2833Control="0"
```

```
tone.dtmf.viaRtp="0"
```

```
voIpProt.SIP.dtmfViaSignaling.rfc2976="1"
```

```
voIpProt.SIP.dtmfViaSignaling.rfc2976.nonLegacyEncoding="1"
```

```
/>
```

```
</tone>
```

```
<voIpProt.SIP.alertInfo
```

```
voIpProt.SIP.alertInfo.3.value="paging" voIpProt.SIP.alertInfo.3.class="autoAnswer"
```

```
voIpProt.SIP.alertInfo.4.value="RDZMQBJf" voIpProt.SIP.alertInfo.4.class="ringAutoAnswer"
```

```
voIpProt.SIP.alertInfo.1.value="external" voIpProt.SIP.alertInfo.1.class="custom1"
```

```
voIpProt.SIP.alertInfo.2.value="internal" voIpProt.SIP.alertInfo.2.class="custom2" />
```

```
<se se.destination="chassis">
```

```
<se.rt>
```

```
<!-- paging section -->
```

```
<se.rt.autoAnswer
```

```
se.rt.autoAnswer.name="Ring Answer"
```

```
se.rt.autoAnswer.type="ring-answer"
```

```
se.rt.autoAnswer.timeout="0"
```

```
se.rt.autoAnswer.ringer="2"
```

```
se.rt.autoAnswer.callWait="6"
```

```
se.rt.autoAnswer.mod="1"/>
```

```
<!-- intercom section -->
```

```
<se.rt.ringAutoAnswer
```

```
se.rt.ringAutoAnswer.name="Ring Answer" se.rt.ringAutoAnswer.type="ring-answer"
```

```
se.rt.ringAutoAnswer.timeout="0"
```

```
se.rt.ringAutoAnswer.ringer="2"
```

```
se.rt.ringAutoAnswer.callWait="6"
```

```
se.rt.ringAutoAnswer.mod="1"/>
```

```
<!-- external ring section -->
```

```
<se.rt.custom1 se.rt.custom1.name="Low Trill" se.rt.custom1.ringer="ringer2"/>
```

```
<!-- internal ring section -->
```

```
<se.rt.custom2 se.rt.custom2.name="Low Trill" se.rt.custom2.ringer="ringer2"/>
```

```
</se.rt>
```

```
</se>
```

```
<call
```

```
call.callWaiting.enable="1"
```

```
call.callWaiting.ring="beep"
```

```
call.rejectBusyOnDnd="1"
```

```
call.enableOnNotRegistered="1"
```

```
call.offeringTimeOut="60"
```

```
call.ringBackTimeOut="60"
```

```
call.lastCallReturnString="*69"
call.callsPerLineKey="24"
call.dialtoneTimeOut="60"
call.transfer.blindPreferred="0"
call.stickyAutoLineSeize="0"
call.stickyAutoLineSeize.onHookDialing="0"
call.singleKeyPressConference="0"
call.localConferenceCallHold="0"
call.directedCallPickupString="*78"
>
<call.shared
  call.shared.disableDivert="1"
  call.shared.seizeFailReorder="1"
  call.shared.oneTouchResume="0"
  call.shared.exposeAutoHolds="1"
/>
  <call.hold>
    <call.hold.localReminder
      call.hold.localReminder.enabled="0"
      call.hold.localReminder.period="60"
      call.hold.localReminder.startDelay="90"
    />
  </call.hold>
</call>
<sec>
  <sec.srtp
    sec.srtp.enable="0"
    sec.srtp.offer="0"
    sec.srtp.require="0"
    sec.srtp.offer.HMAC_SHA1_80="0"
    sec.srtp.offer.HMAC_SHA1_32="0"
    sec.srtp.key.lifetime="0"
    sec.srtp.mki.enabled="0"
    sec.srtp.sessionParams.noAuth.offer="0"
    sec.srtp.sessionParams.noAuth.require="0"
    sec.srtp.sessionParams.noEncrypRTCP.offer="0"
    sec.srtp.sessionParams.noEncrypRTCP.require="0"
    sec.srtp.sessionParams.noEncrypRTP.offer="0"
    sec.srtp.sessionParams.noEncrypRTP.require="0"
    sec.srtp.requireMatchingTag="0" />
  </sec>
</polycomConfig>
```